



Nacional

SAFETY VALVES

Making safety since 1976



PRODUCTION, R+D+I, EVOLUTION

VALVULAS NACIONAL, S.A. was established in Spain in 1976. The main target was to assist the petrochemical and chemical industries emerging in Spain at that time. Right from the start VALVULAS NACIONAL, S.A., has been designing and producing safety valves according to most recognized international standards and norms: API, ASME, ASTM and the European directives 2014/68/UE and 2014/34/UE. Our production process is accredited by an ISO 9001-2015 certification.

Our know how and capacity to adapt to the constantly changing demands of the market, made possible the introduction of new products designed for new applications on the market, like THERMOSOLAR PLANTS, where VALVULAS NACIONAL has supplied safety valves to more than 31 complete plants all over the world, while at the same time continuously supplying to all main companies of the Spanish petrochemical, chemical and refining industries.

PRODUCTION CAPACITY

VALVULAS NACIONAL, S.A. valves' have their discharge coefficients approved in laboratory tests, in order to guarantee and assure that correct values are being used for every sizing process.

In our Technical sales department we have a modern software which allows us to verify all the possibilities, and to assure strict fulfillment of all international standards.

VALVULAS NACIONAL, S.A. has established representation agreements with the most important O.E.M. companies in the safety sector of the industry, consolidating us as one of the main companies by product range; design and consulting in new plants or in new process.

Our continuous growth, shows a clear trend, which confirms the integration of our workers to provide first class service to our customers and partners.

FACTORY & LOCATION

Our facilities in Rubí (Barcelona - Spain), with more than 3.000 Sq m are fully prepared for our production activities: machining with modern CNC, assembling and testing. We also have long term agreements with approved workshops, which provides us with flexibility and fast feedback to customers demands, with full quality guarantee which has always been our main target.

STRATEGIC ALLIANCES

Nowadays VALVULAS NACIONAL, S.A. starts an internationalization process, establishing representation agreements in different countries and continents all over the world, with specialized companies that will provide added value in our service towards the end user.

VALVULAS NACIONAL Making safety since 1976!

MOD-6400

Safety Valve Model 64

Safety valve 90° angular type for fast opening (pop action), full nozzle, spring loaded, adjusting ring, conventional or balanced.

DESIGN: ISO 4126-1 | ASME VIII D.1 | API-526 | ASME 16.34

DIMENSIONS: 1" X 2" UP TO 12" X 16"

FLANGES: INLET 150 ÷ 2500# OUTLET 150 ÷ 300#

(ALSO AVAILABLE IN DIN EXECUTION.)

MATERIALS: CARBON STEEL, STAINLESS STEEL AND SPECIAL ALLOYS



MOD-5100

Safety Valve Model 5100

Safety valve 90° angular type of rapid opening (pop action), full nozzle, and spring loaded, adjusting ring, conventional or balanced.

DESIGN: EN ISO 4126-1 | ASME VIII | API-526 | ASME B16.34

DIMENSIONS: 1/2" X 3/4" UP TO 1" X 1"

THREAD: CONNECTIONS: NPT M&F ANSI B1.20; BSP-BS 21

FLANGES: INLET 150 TO 2500, OUTLET 150 TO 300, ASME 16.5

(ALSO AVAILABLE IN DIN EXECUTION.)

MATERIALS: CARBON STEEL, STAINLESS STEEL & SPECIAL ALLOYS



MOD-3-50

Safety Valve Model 3-50

Safety valve 90° angular type for fast opening (pop action), full nozzle, spring loaded, adjusting ring.

DESIGN: EN ISO 4126-1 | ASME VIII

DIMENSIONS: 1/2" X 3/4" UP TO 1" X 1"

SCREWED: CONNECTIONS: NPT M&F ANSI B1.20; BSP-BS 21

MATERIALS: STAINLESS STEEL



MOD-3-51

Safety Valve Model 3-51

Safety valve 90° angular type for fast opening (pop action), full nozzle, spring loaded, adjusting ring, conventional or balanced, screwed or flanged.

DESIGN: EN ISO 4126-1 | ASME VIII

DIMENSIONS: 1/2" X 3/4" UP TO 1" X 1"

SCREWED: CONNECTIONS: NPT M&F ANSI B1.20; BSP-BS 21

FLANGED: INLET 150 TO 2500, OUTLET 150 TO 300, ASME 16.5

(ALSO AVAILABLE IN DIN EXECUTION.)

MATERIALS: CARBON STEEL, STAINLESS STEEL AND SPECIAL ALLOYS.



MOD-5500

Safety Valve Model 55


Safety valve 90° angular type for fast opening (pop action), semi nozzle, spring loaded.

DIMENSIONS: DN20 X32 UP TO DN150X250

FLANGES: INLET PN 16 TO PN 40, OUTLET PN 16

(ALSO AVAILABLE IN ANSI B16.5 FLANGES)

MATERIALS: CARBON STEEL & STAINLESS STEEL (904L, HASTELLOY, ETC)



PILOT OPERATED

Safety Valve MVP64

Pilot operated pressure relief valve able to operate at considerably higher set pressure than with spring loaded safety relief valves, the valve operation and lift are unaffected by back-pressure.

DIMENSIONS: EN ISO-4126-1 & ASME VIII Div. 1

SIZES AND ASME :1" x 2" up to 8" x 10"

RATINGS : EN/ISO: DN-25 x DN-50 up to DN-200 x DN-250

MATERIALS: ASME/ASTM & EN



MOD-2000

Emergency Valve Model 2000

The emergency valve, model "PH", is a safety device intended for installation on storage tanks with the aim of assure a quick evacuation of large volume of fluid inside the tank in the event of an overpressure due to fire condition


DESIGN: ASME B16.34, EN 1092-1, API 650, API 2000

DIMENSIONS: 16" / DN400

20" / DN500

24" / DN600

MATERIALS: STAINLESS STEEL



MOD-3400

Breather Valve Model 3400

The model 3400, is a pressure relief valve for overpressure nections. This valve is categorized in three different types: Breather, Vacuum and Breather/Vacuum combined.

DESIGN: ASME B16.34, EN 1092-1, API 650, API 2000

DIMENSIONS: DN50 UP TO DN250

2" UP TO 10"

24" / DN600

MATERIALS: STAINLESS STEEL





MOD-6400
ASME UV
SAFETY
VALVE



MOD-5100
ASME UV
SAFETY
VALVE



MOD-3-50
SAFETY
VALVE



MOD-3-51
SAFETY
VALVE



MOD-5500
SAFETY
VALVE



PILOT
OPERATED
SAFETY
VALVE



MOD-2000
EMERGENCY
VALVE



MOD-3400
BREATHING
VALVE



VALVE
SILENCER

Making safety since 1976



C/ Compositor Vivaldi, 2-8, Pol. Ind Can Jordi
08191 Rubí (Barcelona) - Spain
Tel.: +34 936 995 200
comercial@valvulasnacional.com

www.valvulasnacional.com



REV. 0 / OCT-2023